



# HYDRAULIC TRACTOR & ATTACHEMENTS

106001

The ASE Hydraulic Tractor is a self-propelled machine. This tractor is designed with hydraulic outputs for powering different attachments. Full hydraulic power with a reinforced hard gear differential. Heavy duty hydraulic drive system allows for smooth transition of speed from a slow crawl to a fast walk.



SEE THE BACK

# Features & Attachments

## Plow Spec - 106500

Weight	93 Lbs
Dimensions	43" x 13" x 29"

1. 35 degree of angle adjustment to the left or right, the plow attachment moves roofing debris or snow out of the way quickly and easily.



## Sweeper Spec

Drive System	Hydraulic / Chain
Brush Types	Poly Coil (106300) Poly Steel (106301)
Angle Adjustment	Up to 35 Degrees
Brush Dimensions	40" Wide x 19" Diagonal
Weight	200 Lbs
Dimensions	48" x 30" x 24"

2. The double swivel caster support wheels allow the operator to sweep lightly or heavily as the situation demands.



## Roof Remover Spec

Blade	15" Angled (206200) 15" Toothed (206201) 24" Angled (206202) 24" Toothed (206203)
Weight	275 Lbs
Dimensions	54" x 31" x 30"

3. A hydraulic motor drives the cutting blade repeatedly between the built up roof and the roof deck lifting it off for easy disposal.



\*Specifications are subject to change without notice.

## Tractor Specifications

Engine	Wheels	Optionals Additions	Dimensions	Weight
13 H.P. Honda	18 x 9.5 Superlug	Electrical Start Foam Filled Tires	64" x 31" x 30"	500 lbs.